

# NEOVAL OIL RUBIN G8

## High-performance cutting oil



Item no. 820 001 Bottle 100 ml



Item no. 820 001 Item no. 820 500 Item no. 820 005



Item no. 820 025 Item no. 820 060 Item no. 820 200

### PRODUCT DESCRIPTION:

Neoval Rubin G8 is an indispensable premium product in the metalworking, plastics, wood, paper and textile sectors. It can replace a whole series of individual products thanks to its versatility as a cutting oil, cutting oil additive, drilling oil, grinding oil, lubricant for machines, tools and chains, hydraulic oil, release agent and preservation product. Additives form a separating layer between the tools, ensuring temperature resistance.

### APPLICATION AREA:

- For the following materials: CrNi, Fe, Ti, Al, cast, non-ferrous metals, precious metals and plastics.
- Can be used for all metals and alloys, even those very difficult to machine
- Boost to production and improved quality, e.g.: surface quality, gloss and chip flow, with prevention of burring, built-up edges and clogging up of slugs and chips.

### BENEFITS:

- reduces friction, temperature and wear
- prevents built-up edges and clogging up
- considerably extends tool life
- free of acids, sulphur and silicone
- can be mixed with all mineral oils
- keeps for at least 10 years if stored correctly
- resistant to high pressures and temperatures (-40°C to +500°C)

### PROPERTIES:

Kinematic viscosity at 40°C: 38-40 mm<sup>2</sup>/s  
SAE viscosity: approx. SAE 20W  
Density at 20°C: approx. 0.99 g/ml

Item no.	Contents	Container	Quantity
820 001	100 ml	Bottle	1 box (contains 24 bottles)
820 500	500 ml	Bottle	1 box (contains 6 bottles)
820 005	5 Lt.	Canister	
820 025	25 Lt.	Canister	
820 060	60 Lt.	Barrel	
820 200	200 Lt.	Barrel	